



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name: ESPRESSO GONFIA RIPARA 75ML
Trade code: A06243
Product type and use: Car maintenance product.
Company:
STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.
Emergency telephone number of the company and/or of an authorised advisory centre:
STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491
Competent person responsible for the safety data sheet:
Montini Vittorino stacplas@stacplastic.com

2. HAZARDS IDENTIFICATION

Properties / Symbols:
F+ Extremely flammable
R Phrases:
R12 Extremely flammable.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components within the meaning of EEC directive 67/548 and corresponding classification:

30% - 40% propane
N.67/548/CEE: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9
F+; R12; substance with a Community workplace exposure limit

15% - 20% butane [1]
N.67/548/CEE: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7
F+; R12; substance with a Community workplace exposure limit

5% - 7% ethanediol
N.67/548/CEE: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3
Xn; R22

5% - 7% and isobutane [2]
N.67/548/CEE: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2
F+; R12; substance with a Community workplace exposure limit

636 mg/kg caustic potash
N.67/548/CEE: 019-002-00-8 CAS: 1310-58-3 EC: 215-181-3
Xn,C; R22-35

4. FIRST AID MEASURES

Contact with skin:
After contact with skin, wash immediately with plenty of... (to be specified by the manufacturer).
Wash with plenty of water and soap.
Contact with eyes:
Wash immediately and thoroughly with running water, keeping eyelids raised, for at least 10 minutes. Following this, protect the eyes with sterile gauze or a clean, dry, handkerchief. OBTAIN A MEDICAL EXAMINATION.
Swallowing:
Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.
A suspension of activated charcoal in water, or liquid paraffin may be administered.
Inhalation:
Ventilate the premises. The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area. Should the patient feel unwell, OBTAIN MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES

Recommended extinguishers:
CO2 or Dry chemical fire extinguisher.
Extinguishers not to be used:
None in particular.
Risks arising from combustion:
Avoid inhaling the fumes.
Protective equipment:
Use protection for the respiratory tract.
Cool the containers exposed to the fire with water.

6. ACCIDENTAL RELEASE MEASURES

Measures for personal safety:
Use gloves and protective clothing.
Environmental measures:

Limit leakages with earth or sand.
Eliminate all unguarded flames and possible sources of ignition. Do not smoke.
If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

Cleaning methods:

If the product is in a liquid form, stop it from entering the drainage system.
Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.
After the product has been recovered, rinse the area and materials involved with water.

7. HANDLING AND STORAGE

Handling precautions:

Avoid contact and inhalation of the vapours. See, too, paragraph 8 below.
Do not eat or drink while working.
Do not smoke while working.

Incompatible materials:

None in particular.

Storage conditions:

Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Respiratory protection:

Not needed for normal use.

Protection for hands:

Not needed for normal use.

Eye protection:

Not needed for normal use.

Protection for skin:

No special precaution must be adopted for normal use.

Exposure limit(s) (ACGIH):

propane

TLV TWA: 1000 ppm

butane [1]

TLV TWA: 1000 ppm

ethanediol

VLE 8h: 52 mg/m³ - 20 ppm VLE short: 104 mg/m³ - 40 ppm TLV TWA: A4 TLV STEL: C 39,39 ppm - C 100 mg/m³, A4

and isobutane [2]

TLV TWA: 1000 ppm

caustic potash

TLV STEL: C 0,87 ppm - C 2 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	Spray can
Odour: ammoniacal	
pH: 9.5 ÷ 10.5	
Melting point:	N.A.
Boiling point:	N.A.
Flash point:	< 0 ° C
Solid/gas flammability:	N.A.
Autoignition temperature:	(gas) > 400°C
Explosive properties:	N.A.
Oxidizing properties:	N.A.
Vapour pressure:	N.A.
Relative density:	1.0 kg/l
Solubility in water:	100%
Partition c. (n-octanol/H ₂ O):	N.A.
Vapour density:	>1

10. STABILITY AND REACTIVITY

Conditions to avoid:

Stable under normal conditions.

Substances to avoid:

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products:

None.

11. TOXICOLOGICAL INFORMATION

The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Set out below is the toxicological information relating to the main substances in the preparation.

ethanediol

LD50 (RABBIT) ORAL: 5017 MG/KG BW

12. ECOLOGICAL INFORMATION

Adopt good working practices, so that the product is not released into the environment.

13. DISPOSAL CONSIDERATIONS

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

14. TRANSPORT INFORMATION

ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950

IATA-Class: 2.1

IMDG-Class: 2 Aerosols UN 1950

IMDG-Page: 2102

15. REGULATORY INFORMATION

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments. Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments. Commission Directive 98/24/EC (Protection of the health and safety of workers from the risk related to chemical agent). Commission Directive 2000/39/EC (Occupational exposure limit values). Regulation (EC) No 1907/2006 (REACH).



F+

Symbols:

F+ Extremely flammable

R Phrases:

R12 Extremely flammable.

S Phrases:

S16 Keep away from sources of ignition - No smoking.

S2 Keep out of reach of children.

S9 Keep container in a well-ventilated place.

Special Provisions:

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of reach of children.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents').

16. OTHER INFORMATION

Text of R phrases referred to under heading 3:

R12 Extremely flammable.

R22 Harmful if swallowed.

R35 Causes severe burns.

Paragraphs modified from the previous revision:

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

2. HAZARDS IDENTIFICATION

3. COMPOSITION/INFORMATION ON INGREDIENTS

4. FIRST AID MEASURES

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

9. PHYSICAL AND CHEMICAL PROPERTIES

13. DISPOSAL CONSIDERATIONS

15. REGULATORY INFORMATION

Main bibliographic sources:

Safety Data Sheet
ESPRESSO GONFIA RIPARA 75ML

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
ACGIH - Threshold Limit Values - 2004 edition

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended. This MSDS cancels and replaces any preceding release.